

CHRYSLER



NOTES:

Part #	Description	Center to Center (IN)	Center to Center (MM)	Style	Bolt Size	Bolt Type	Pin Width (IN)	Pin Width (MM)	Big Width (IN)	Big Width (MM)	Big Bore (IN)	Big Bore (MM)	Total/Rotate/Recip / Weight (gr)	Pin Size	Cyl
S675NEWCN12MM1094	HEMI	6.750	171.45	I BEAM	12MM	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	862 / 582 / 280	1.094	8
S6875C12MM1094	AJPE 481X	6.875	174.63	I BEAM	12MM	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	868 / 587 / 281	1.094	8
J6760NOS	440	6.760	171.70	I BEAM	7/16"	R&R2000 / L19	1.198	30.43	0.990	25.15	2.325	59.06	694 / 474 / 220	0.990	8
S6900A	HEMI	6.900	175.26	I BEAM	7/16"	L19 / CA 625	1.400	35.56	1.000	25.40	2.500	63.50	808 / 538 / 270	1.094	8
392HEMIMOTORPLEX	392 HEMI	7.020	178.31	I BEAM	7/16"	L19	1.380	35.05	0.980	24.89	2.500	63.50	705 / 479 / 226	1.094	8
J7100MWH	440	7.100	180.34	I BEAM	7/16"	R&R L19	1.195	30.35	1.005	25.53	2.500	63.50	721 / 509 / 212	0.990	8
S6676NEWCN12MM1094	HEMI	6.676	169.57	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	854 / 578 / 276	1.094	8
S6700NEWCN12MM1094	HEMI	6.700	170.18	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	861 / 584 / 277	1.094	8
S6706NEWCN12MM1094	HEMI	6.706	170.33	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	854 / 578 / 276	1.094	8
S6735NEWCN12MM1094	HEMI	6.735	171.07	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	862 / 582 / 280	1.094	8
S6740NEWCN12MM1094	HEMI	6.740	171.20	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	869 / 587 / 282	1.094	8
S6750NEWCN12MM1094	HEMI	6.750	171.45	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	863 / 583 / 280	1.094	8
S6763NEWCN12MM1094	HEMI	6.763	171.78	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	863 / 583 / 280	1.094	8
S6800NEWCN12MM	HEMI	6.800	172.72	I BEAM	12mm	R&R L19	1.202	30.53	1.013	25.73	2.500	63.50	851 / 589 / 262	1.094	8
S6820NEWCN12MM1094	HEMI	6.820	173.23	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	870 / 586 / 284	1.094	8
S6840NEWCN12MM1094	HEMI	6.840	173.74	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	873 / 589 / 284	1.094	8
S6850NEWCN12MM1094	HEMI	6.850	173.99	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	869 / 585 / 284	1.094	8

CHRYSLER



NOTES:

CONTINUED

Part #	Description	Center to Center (IN)	Center to Center (MM)	Style	Bolt Size	Bolt Type	Pin Width (IN)	Pin Width (MM)	Big Width (IN)	Big Width (MM)	Big Bore (IN)	Big Bore (MM)	Total/Rotate/Recip / Weight (gr)	Pin Size	Cyl
S7280NEWCN12MM1094	HEMI	7.280	184.91	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	894 / 597 / 297	1.094	8
S7290NEWCN12MM1094	HEMI	7.290	185.17	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	895 / 598 / 297	1.094	8
S7300NEWCN12MM1094	HEMI	7.300	185.42	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	892 / 596 / 296	1.094	8
S7306NEWCN12MM1094	HEMI	7.306	185.57	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	897 / 599 / 298	1.094	8
S7315NEWCN12MM1094	HEMI	7.315	185.80	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	893 / 597 / 296	1.094	8
S7320NEWCN12MM1094	HEMI	7.320	185.93	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	902 / 601 / 301	1.094	8
S7330NEWCN12MM1094	HEMI	7.330	186.18	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	902 / 602 / 300	1.094	8
S7351NEWCN12MM1094	HEMI	7.351	186.72	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	898 / 599 / 299	1.094	8
S7403NEWCN12MM1094	HEMI	7.403	188.04	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	898 / 599 / 299	1.094	8
S7531NEWCN12MM1094	HEMI	7.531	191.29	I BEAM	12mm	R&R L19	1.400	35.56	1.000	25.40	2.500	63.50	913 / 606 / 307	1.094	8
T6890KNP	HEMI	6.890	175.01	SOLID	7/16"	R&R2000 / L19	1.525	38.74	1.000	25.40	2.500	63.50	983 / 617 / 366	1.156	8

CHRYSLER





6601 TAYLOR ROAD UNIT A
PUNTA GORDA, FL. 33950

1-941-621-8143

EMAIL: Info@rrconnectingrods.com

WEBSITE: www.rrconnectingrods.com